

## General Description

3101 is a clear gloss concrete and masonry surface sealer and cure coating specially formulated of acrylic polymers in a VOC compliant solvent solution. This coating is outstanding in its ability to protect surfaces from staining and discoloration.

## Uses

Exterior use only. Very effective on exposed aggregate, concrete or concrete pavers to achieve the "wet look" and to minimize discoloration caused by the rough texture, trapping dirt particles. Clearcoat is an excellent all round weather proofing coating. Effective sealer for terazzo, stone, slate and unglazed tiles.

Clearcoat is a protective coating for concrete and other substrates against occasional spills of acids, alkalis, food acids, oil, water based paints, wet concrete, etc.

## Physical Properties

Appearance	-	Water white clear liquid
Density (25°C)	-	0.91 kg/litre (7.6 lb/gallon)
Dry Film Appearance	-	15 to 30 minutes
Coverage	-	150 to 200 ft <sup>2</sup> per gallon
Solids	-	15%

## Application Instructions

Apply to fresh concrete when the surface sheen has disappeared completely. Apply by roller or low pressure sprayer. Caution should be used when rolling at temperatures above 20°C. Treat vertical surfaces immediately after stripping forms. For application to existing concrete, all surfaces must be clean, dry, and free of contaminants such as oil, grease, dirt and other deleterious materials.

Ready to use. Do not thin.

Refer to MSDS for information on protective equipment.

Cleanup tools with Xylene or Resolve.

## Compliance

Clearcoat is recommended for all classes of concrete floors as classified in Table 1.1, ACI Standard 302.1R-89. Meets or exceeds ASTM C 309.

## Packaging

Available in 3.78 litre ( 1 U.S. gallon), 18.93 litre (5 U.S. gallon), and 205 litre (55 gallon) containers.