

## General Description

310230 is a clear, high gloss, non-yellowing concrete and masonry surface sealer specially formulated of acrylic polymers in a solvent solution. This coating is outstanding in its ability to protect surfaces from staining and discoloration.

## Uses

Exterior - Very effective on exposed aggregate, concrete or concrete pavers to achieve the "wet" look and to minimize discoloration caused by the rough texture trapping dirt particles. Excellent all round weather proofing coating. Effective sealer for terazzo, stone, slate and unglazed tiles.

Interior - Floor sealer and dust proofer. Protective coating for concrete and other substrates against occasional spills of acids, alkalis, food acids, oil, water based paints, wet concrete, etc.

## Physical Properties

Appearance	-	Clear liquid
Density (25°C)	-	1.01 kg/litre (9 lb/U.S. gallon)
Dry Film Appearance	-	Clear
Drying Time (21°C)	-	1 to 2 hours
Coverage	-	25 - 40 square feet per litre (90 to 150 sq ft./U.S. gal)
Solids	-	30%

## Application Instructions

Make sure surface is free of oil and dirt. This can be achieved by scrubbing with a soap solution of trisodium phosphate or Pavclean solution. After cleaning, rinse the surface thoroughly and let dry. Apply 310230 by spray, brush or roller.

## Clean Up

Tools can be cleaned up with xylene after use.

## Packaging

Available in 3.78 ltr (1 U.S. gal), 18.93 ltr (5 U.S. gal), and 205 ltr (55 U.S. gal.) drums.